

Hasselblad September, 2015

Firmware version 2.6.5R for CCD based H5D cameras

This package contains firmware version 2.6.5R for all CCD based H5D cameras.

Changes since version 2.5.4R:

- Solves a rare issue where a tethered capture could result in black images
- Stability improvements
- Internal production support

Installation

Manual updating of firmware is available in the Phocus software, from version 2.7 Mac and 2.7 Windows. However, please use the latest version of Phocus for firmware updating. For Windows it is strongly recommended to use the 64 bit version.

Procedures for updating capture unit firmware via the Phocus software:

1. Unzip the downloaded file.
2. Make sure your camera is turned on.
3. Connect your complete camera, including the capture unit, lens and viewfinder to Phocus using a POWERED FireWire cable.
4. Go to "File" and then "Update Firmware" and locate the desired firmware package (firmware_2_6_5R.cim) on your computer, and click "Update".
5. Follow the instructions provided from the software carefully! Do not switch off the camera during the update process, unless specifically requested by the Phocus software.
6. When the update has been finalized, please restart your camera and check that the firmware has been successfully updated.

IMPORTANT NOTICE: During the upgrade procedure do NOT disconnect the FireWire cable until prompted!

Unintentionally removing the FireWire cable during the firmware download procedure could in worst case render the camera useless which would require the need for authorized service.