

Hasselblad
Jan 08, 2014

Firmware version 2.5.4R for all H5D camera models

This package contains firmware version 2.5.4R.

Changes since version 2.4.3R:

- Support for technical cameras using Rollei or Schneider electronic shutters
- Image orientation sensor now works as in the H4D (Auto setting)
- Live Video for all models
- Stability improvements and minor cosmetic corrections

Installation

Manual updating of firmware is available in the Phocus software, from version 2.7 Mac and 2.7 Windows.

Procedures for updating capture unit firmware via the Phocus software:

1. Unzip the downloaded file.
2. Make sure your camera is turned on.
3. Connect your complete camera, including the capture unit, lens and viewfinder to Phocus using a POWERED Firewire cable.
4. Go to "File" and then "Update Firmware" and locate the desired firmware package (H5D_254R.cim) on your computer, and click "Update".
5. Follow the instructions provided from the software carefully! Do not switch off the camera during the update process, unless specifically requested by the Phocus software.
6. When the update has been finalized, please restart your camera and check that the firmware has been successfully updated.

IMPORTANT NOTICE: During the upgrade procedure do NOT disconnect the firewire cable until prompted!

Unintentionally removing the Firewire cable during the firmware download procedure could in worst case render the camera useless which would require the need for authorized service.

Change Log:

Changes in version 2.4.3R:

- Low battery warning on sensor unit display
- High temperature warning
- Double click on release button enters menu on sensor unit display
- Support for GPS module (GIL)
- Technical camera mode (Flash sync and pinhole)
- Folder view
- Faster start-up time
- Improved histogram
- Improved 9-view
- Language support: English, Spanish, French, German, Italian, Japanese, Chinese

Changes in version 2.3.3R: (H5D-60 only)

- First release

Changes in version 1.5.8R (H5D-40, H5D-50, H5D-50MS and H5D-200MS):

New features:

- Support for multi-shot

Changes in version 1.5.3R (H5D-40 and H5D-50):

New features:

- Nine image view now available
- Visual indication of overexposed areas in the image (Mark overexposure) now available
- Chinese language support
- Numerous bug fixes and stability improvements

Changes in version 1.2.0R (H5D-40 and H5D-50):

New features:

- Improved color rendition in high ISO JPEG
- Various Graphical User Interface improvements
- Performance improvements